Dimension and Wall Thickness to ANSI R26 10/R26 10

1016

1066.8

1117.6

1168.4

1219.2

40

42

44

46

48

Dime	Dimension and Wall Thickness to ANSI B36.19/B36.10																	
NPS	OD(mm)	sch5s	sch10s	sch10	sch20	sch30	sch40s	STD	sch40	sch60	sch80s	XS	sch80	sch100	sch120	sch140	sch160	XXS
1/8	10.3		1.24				1.73	1.73	1.73		2.41	2.41	2.41					
1/4	13.7		1.65				2.24	2.24	2.24		3.02	3.02	3.02					
3/8	17.1		1.65				2.31	2.31	2.31		3.2	3.2	3.2					
1/2	21.3	1.65	2.11				2.77	2.77	2.77		3.73	3.73	3.73				4.78	7.47
3/4	26.7	1.65	2.11				2.87	2.87	2.87		3.91	3.91	3.91				5.56	7.82
1	33.4	1.65	2.77				3.38	3.38	3.38		4.55	4.55	4.55				6.35	9.09
1 1/4	42.2	1.65	2.77				3.56	3.56	3.56		4.85	4.85	4.85				6.35	9.7
1 1/2	48.3	1.65	2.77				3.68	3.68	3.68		5.08	5.08	5.08				7.14	10.15
2	60.3	1.65	2.77				3.91	3.91	3.91		5.54	5.54	5.54				8.74	11.07
2 1/2	73	2.11	3.05				5.16	5.16	5.16		7.01	7.01	7.01				9.53	14.02
3	88.9	2.11	3.05				5.49	5.49	5.49		7.62	7.62	7.62				11.13	15.24
3 1/2	101.6	2.11	3.05				5.74	5.74	5.74		8.08	8.08	8.08					
4	114.3	2.11	3.05				6.02	6.02	6.02		8.56	8.56	8.56		11.13		13.49	17.12
5	141.3	2.77	3.4				6.55	6.55	6.55		9.53	9.53	9.53		12.7		15.88	19.05
6	168.3	2.77	3.4				7.11	7.11	7.11		10.97	10.97	10.97		14.27		18.26	21.95
8	219.1	2.77	3.76		6.35	7.04	8.18	8.18	8.18	10.31	12.7	12.7	12.7	15.09	18.26	20.62	23.01	22.23
10	273.1	3.4	4.19		6.35	7.8	9.27	9.27	9.27	12.7	12.7	12.7	15.09	18.26	21.44	25.4	28.58	25.4
12	323.9	3.96	4.57		6.35	8.38	9.53	9.53	10.31	14.27	12.7	12.7	17.48	21.44	25.4	28.58	33.32	25.4
14	355.6	3.96	4.78	6.35	7.92	9.53		9.53	11.13	15.09		12.7	19.05	23.83	27.79	31.75	35.71	
16	406.4	4.19	4.78	6.35	7.92	9.53		9.53	12.7	16.66		12.7	21.44	26.19	30.96	36.53	40.49	
18	457.2	4.19	4.78	6.35	7.92	11.13		9.53	14.27	19.05		12.7	23.83	29.36	34.93	39.67	45.24	
20	508	4.78	5.54	6.35	9.53	12.7		9.53	15.09	20.62		12.7	26.19	32.54	38.1	44.45	50.01	
22	558.8	4.78	5.54	6.35	9.53	12.7		9.53		22.23		12.7	28.58	34.93	41.28	47.63	53.98	
24	609.6	5.54	6.35	6.35	9.53	14.27		9.53	17.48	24.61		12.7	30.96	38.89	46.02	52.37	59.54	
26	660.4			7.92	12.7			9.53				12.7						
28	711.2			7.92	12.7	15.88		9.53				12.7						
30	762	6.35	7.92	7.92	12.7	15.88		9.53				12.7						
32	812.8			7.92	12.7	15.88	17.48	9.53	17.48			12.7						
34	863.6			7.92	12.7	15.88	17.48	9.53	17.48			12.7	Com	monte:	SCHES 11	ne ane ea	ns are use	nd for
36	914.4			7.92	12.7	15.88	19.05	9.53	19.05			12.7	Stainlace Staal Dings and Littings //SI/IL///IISI					
38	965.2							9.53				12.7						

9.53

9.53

9.53

9.53

9.53

B36.19/B36.10

12.7

12.7

12.7

12.7

12.7